



(11) Publication number : **0 627 359 A1**

(12)

EUROPEAN PATENT APPLICATION

(21) Application number : **94500094.1**

(51) Int. Cl.⁶ : **B65D 49/04, B65D 49/02**

(22) Date of filing : **27.05.94**

(30) Priority : **31.05.93 ES 9301178**

(43) Date of publication of application :
07.12.94 Bulletin 94/49

(84) Designated Contracting States :
DE FR GB GR IE IT PT

(71) Applicant : **Junqueras Guerre, Joaquín**
C. del Riu, 27
E-08291 Ripollet (Barcelona) (ES)

(72) Inventor : **Junqueras Guerre, Joaquín**
C. del Riu, 27
E-08291 Ripollet (Barcelona) (ES)

(74) Representative : **Pontí Sales, Adelaida Oficina**
Pontí et al
Passeig de Gràcia, 33
E-08007 Barcelona (ES)


(54) **Bottle stopper with a safeguard against unauthorized refilling.**

(57) An non-fillable stopper (1) comprising a first tubular body or vessel (4), a second body or pourer (14), and a third body or skirt (22) arranged outside the neck (2) of the bottle (3); said vessel (4) comprising a guide (6) and openings (5), forming a first chamber (7) which comprises a plug (9) that can move along the guide (6) and a seated opening (8); said second body (14) forming a second chamber (18); and said third body (22) comprising fixing means, joining means and a cap (24) with tearable means (23). It is characterized in that it comprises an element (19), resistant to penetration by piercing objects, arranged inside the second chamber (18).

The movable plug element (9) comprises a cylindrical part (10) which fits in the opening of the seat (8).

It further comprises inclined flexible elements (21) arranged between the pourer (14) and the openings (5).

It prevents bottles from being refilled.



The present invention relates to a non-fillable stopper. Said non-fillable stopper is for use in bottles in which the pouring of liquids does not imply the possibility of gaining access to the interior thereof, preventing fraudulent refilling.

BACKGROUND OF THE INVENTION

The use of non-fillable stoppers as a means of protecting and ensuring inviolability of the interior of bottles is a widely known field in which innovations appear constantly. Said innovations are a result of the continuing advances in the fraudulent activities relating to the refilling of bottles containing drinks, a practice which must be prevented at all costs.

For this reason there is a great deal of documentation, references and records describing embodiments of non-fillable stoppers, among which it is worth mentioning the following Spanish utility models:

- U 159124 for a "Bottle closing device".
- U 194560 for a "Irreversible axial coupling safety closure for liqueur bottles and other receptacles".
- U 250124 for a "Arrangement to prevent fraudulent opening of non-fillable stoppers".
- U 289887 for a "Bottle closing device" and patent
- PE 8701859 for Improvements in non-fillable stoppers".

These documents describe different embodiments of non-fillable stoppers, all of them with similar characteristics such as the fact that they comprise a body fitted inside the mouth of the bottle, and that they are provided with a housing in the form of a cage inside which is arranged a plug valve that tends to remain in its seat, closing the liquid outlet opening, when the bottle is upright.

Current non-fillable stoppers have demonstrated their effectiveness, but they no longer manage to prevent entirely improper tampering or the fraudulent refilling of bottles.

These current stoppers offer little protection against access by piercing elements, such as hypodermic needles, nails, etc., which makes it possible to tamper with the plug valve and eliminate its tendency to remain in its seat, thereby allowing access to the interior of the bottle.

Another known fraudulent practice is the insertion of metal pipes or tubes of small diameter at a high temperature such that they easily penetrate the various components, which are normally made of plastic, forming an opening which allows access to the interior of the bottle.

It is also known that the valve and its seat are not one hundred percent watertight, and that said watertightness can be easily overcome, since the valve oscillates and rocks in its seat, allowing access to the interior of the bottles during such rocking motion.

Finally, a common fraudulent practice is to extract entirely the assembly comprising the non-fillable stopper and the means by which it is fitted to the bottle, leaving the neck of the bottle free for fraudulent refilling.

Said practices are known and it is for this reason that non-fillable stoppers have improvements and innovations which tend on the one hand to avoid said undesirable tampering and on the other to improve the conditions of inviolability and make it more difficult to gain access to the interior of the bottles.

It is therefore also important to point out that any non-fillable stopper should provide suitable conditions regarding the inviolability and difficulty of access to the interior of the bottle, without these conditions making it too expensive to realize or difficult to carry out and without having a negative effect on normal pouring actions, in particular regarding the fluidity of pouring.

DESCRIPTION OF THE INVENTION

In order to solve the above mentioned drawbacks, the non-fillable stopper which forms the object of the present invention has been conceived.

Said stopper comprises a first tubular body or vessel which fits hermetically into the mouth of the neck of a bottle or the like, a second pouring body or element, joined to the first body, and a third body or skirt arranged outside the neck of the bottle and which fixes the other two bodies, which are connected together, to the neck of the bottle.

The first tubular body or vessel comprises a movement guide and a plurality of openings. Said first tubular body or vessel forms a first chamber which inside comprises a plug element that can move along the movement guide and a seated opening for said plug element.

The second body, connected to the first body, forms a second chamber juxtaposed to the first chamber.

The third body comprises means of fixing it to the neck of the bottle, means of joining it to the assembly formed by the first and second bodies and a cap for closing the assembly, said cap being linked to the third body by tearable means.

The non-fillable stopper which forms the object of the invention is characterized in that it comprises an element, made of a material which is resistant to penetration by piercing objects, arranged inside the second chamber in such a way that it prevents access to the first chamber.

Said element prevents and hinders piercing elements from gaining access to the interior of the stopper and therefore the movable plug element.

Advantageously, the element which prevents access to the first chamber is a sphere, making it very much more difficult for piercing elements such as hypo-

dermic needles or nails to penetrate.

According to one preferred embodiment, the stopper is characterized in that the movable plug element comprises a cylindrical part which penetrates the opening in the seat of the plug element, fitting in said opening, when the bottle is in the rest position.

This improves the fitting of the plug element in the seat of the opening, preventing oscillating movements of the plug element.

Preferably, the cylindrical part of the plug element comprises a peripheral channel into which fits the seat of the opening.

This prevents undesirable inclinations of the plug element when it is in the position for closing the opening.

According to another embodiment, the non-fillable stopper comprises a plurality of inclined flexible elements arranged between the second body and the plurality of openings in the first chamber of the first body. Said inclined elements move in order to allow the liquid inside to come out and to prevent the entrance of liquids from the outside.

Said elements constitute a unidirectional valve of simple design and low cost.

Advantageously, the plurality of inclined flexible elements are inside the first body and arranged in such a way that they are inaccessible from the outside.

This prevents said elements from being tampered with.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the present invention be better understood, the accompanying drawings show by way of non-limiting example one practical embodiment of a non-fillable stopper according to the present invention.

Figure 1 is an elevation view, sectioned along its axis of symmetry, of an assembly of elements of the non-fillable stopper which forms the object of the invention, arranged on a bottle and in the closed position.

Figure 2 is an elevation view, sectioned along its axis of symmetry, of the complete assembly of the non-fillable stopper arranged on the bottle and in the same closed position as in figure 1.

Figure 3 shows the assembly of elements of figure 1, arranged on the bottle and in the position in which liquid from inside the bottle can flow out.

DESCRIPTION OF A PREFERRED EMBODIMENT

Figures 1 and 2 show an embodiment of the non-fillable stopper 1 arranged on the neck 2 of a bottle 3. Said stopper 1 comprises a first body 4, comprising a number of openings 5 and a guide rod 6, all moulded in a single piece and forming a chamber, known as the

vessel 17, which is housed inside the neck 2 of the bottle 3. The vessel 7 is provided in its lower part with a seated opening 8 for the passage of liquid.

A valve 9 is provided inside said vessel 7, said valve comprising a cylindrical body 10, which fits by means of a peripheral channel 11 in the seated opening 8, and a head 12 whose diameter is larger than the cylindrical body 10 and therefore larger than the seated opening 8. Said valve 9 further comprises a central hole 13 through which the guide rod 6 can pass.

The non-fillable stopper further comprises a second body known as the pourer 14 which, being moulded in a single piece, comprises an outer cylinder 15 with various protruding ribs 16, 17, being connected to the first body 4 and positioned above the neck 2 of the bottle 3 and forming, together with the first body, another chamber 18, tronco-conical in shape, in which is located a sphere 19.

A ring 20 with inclined flexible elements 21 is arranged between the two bodies 4 and 14, said elements resting, in their normal position, against the various openings 5 of the body 4 and preventing the passage of liquid from the outside, and being able to bend away from said openings 5 when the liquid comes from the body 4.

Finally, said stopper comprises a ring known as the skirt 22 which, being fixed to the outside of the neck 2 of the bottle 3 and being joined to the ribs 16 of the outer cylinder 15 of the pouring body 14, which is in turn joined to the body 4, secures and fixes the elements of the stopper to the neck 2 of the bottle 3.

In a non-permanent way by means of a tearable ring 23, said skirt forms an integral part of a closing cap 24 which in turn is provided with a number of ribs 25 by which it is coupled to the rib 17 of the outer cylinder 15.

The arrangement of the elements of the non-fillable stopper enables liquid to leave the bottle 3 by removing the closing cap 24 and placing said bottle 3 in a position for pouring the liquid, as shown in figure 3. The valve 9 moves along the rod 6, due to the effect of gravity, until it reaches the end of the body 4. The liquid from inside the bottle 3 enters the vessel 7 and passes through the openings 5, pressing against the flexible elements 21 and bending them so as to allow the liquid to flow outside via the pouring element 14.

Furthermore, the same arrangement of the elements of the stopper prevents the bottle from being refilled.

The sphere prevents piercing elements from penetrating inside the vessel 7 since, as it is free inside the chamber 18 and being made of hardened materials and having no static surfaces, it makes it difficult or impossible for a piercing element to penetrate via the space defined by the chamber 18.

The inclined elements 21 are inaccessible from the outside and prevent the passage of liquids from the outside to the inside of the bottle 3 should the op-

eration of the valve 9 be violated.

Finally, the possible refilling of the bottle by means of shaking or oscillating movements is prevented since said valve arranged in the seated opening 8 has a design which produces a stable and watertight seal with said opening.


A concrete embodiment of the invention has been described by way of example, although the non-fillable stopper which forms the object of the invention is subject to numerous modifications and variations, obvious to an expert in the field, which should be considered as included within the scope of the inventive concept and of the accompanying claims.


Claims


1. An non-fillable stopper (1) comprising a first tubular body or vessel (4) which fits hermetically into the mouth of the neck (2) of a bottle (3) or the like, a second pouring body or element (14), joined to the first body (4), and a third body or skirt (22) arranged outside the neck (2) of the bottle (3) and which fixes the other two bodies (4, 14), which are connected together, to the neck (2) of the bottle; said first tubular body or vessel (4) comprising a movement guide (6) and a plurality of openings (5) and said first body (4) forming a first chamber (7) which inside comprises a plug element (9) that can move along the movement guide (6) and a seated opening (8) for said plug element (9); said second body (14), joined to the first body (4), forming a second chamber (18) juxtaposed to the first chamber (7); and said third body (22) comprising means of fixing it to the neck of the bottle, means of joining it to the assembly formed by the first and second bodies (4, 14) and a cap (24) for closing the assembly, said cap being linked to the third body (22) by tearable means (23), characterized in that it comprises an element (19), made of a material which is resistant to penetration by piercing objects, arranged inside the second chamber (18) in such a way that it prevents access to the first chamber (7).
2. A stopper according to claim 1, characterized in that the element which prevents access to the first chamber (7) is a sphere (19).
3. A stopper according to the previous claims, characterized in that the movable plug element (9) comprises a cylindrical part (10) which penetrates the opening in the seat (8) of the plug element (9), fitting in said opening, when the bottle (3) is in the first position.
4. A stopper according to claim 3, characterized in that the cylindrical part (10) of the plug element

(9) comprises a peripheral channel (11) into which fits the seat (8) of the opening.

5. A stopper according to the previous claims, characterized in that it comprises a plurality of inclined flexible elements (21) arranged between the second body (14) and the plurality of openings (5) in the first chamber (7) of the first body (4), said inclined elements (21) moving in order to allow the liquid inside to come out and to prevent the entrance of liquids from the outside.
6. A stopper according to claim 5, characterized in that the plurality of inclined flexible elements (21) are inside the first body (4) and arranged in such a way that they are inaccessible from the outside.









European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 94 50 0094

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CLS)
Y A	GB-A-2 088 317 (KOLB) * page 2, line 1 - page 3, line 51; figures 1,5,11 * ---	1-3,5,6 4	B65D49/04 B65D49/02
Y	GB-A-2 251 846 (MONTGOMERY) * page 3, line 24 - page 7, line 1; figures 1,3-6 * ---	1-3,5,6	
Y A	GB-A-1 399 840 (BETTS) * page 2, line 10 - page 3, line 39; figures 1-3 * ---	3 1	
A	DE-C-95 333 (ROBERT PESONNE DE SENNEVOY) * the whole document * ---	1	
Y	DE-C-108 574 (POOLE) * claim; figures 1-3 * ---	2	
A	GB-A-25 372 (CHARTRAND) * page 2, line 21 - line 29; figure 1 * ---	2	
Y	FR-A-379 525 (CORTRIGHT) * page 1, line 24 - line 57; figures 1-3 * ---	5,6	TECHNICAL FIELDS SEARCHED (Int.CLS) B65D
A	FR-A-348 596 (PHILIPPON) * page 1, line 36 - line 58; figures 1,2 * -----	5,6	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 22 August 1994	Examiner Newell, P
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 01.82 (P04C01)